

XL 635

Multimedia Projector

Business & Education



The Specktron XL 635 offers outstanding image quality powered by 3,500 ANSI lumens. The device is loaded with features including auto keystone correction and 15000:1 contrast ratio. These features and more are all packed into a light weight, compact design to deliver on-site presentations, anywhere.

KEY FEATURES

Technology	3LCD
Brightness	3500 Ansi Lumens
Resolution	XGA (1024 x768)
Contrast Ratio	15000:1
Lamp Life	10000 hrs(Eco)
Net Weight	3.2 kg



SPECIFICATIONS

Display Technology	3LCD, 3 - Chip technology
Native Resolution	XGA (1024x768)
Brightness(Lumens)	3500
Contrast Ratio	Upto 15000:1 Dynamic
Lamp	Philips 218W
Lamp Life	5000 hrs(Normal)/ 10000 hrs(Eco)
Projection Lens	F:1.6-1.76 F=19,158-23,018mm
Throw Ratio	70"@2.1m ; 1.48-1.78 : 1
Colour Uniformity	80%
Screen size	0.888-10.937m (30"-300")
Aspect Ratio	4:3 (Standard)/16:9(Compatible)
Keystone Correction	V: 30° (auto+manual) H : 15° (manual) Pincushion/Barrel Correction Corner Keystone
Input	VGA*2 Audio in (mini jack,3.5mm)*1 YCbCr/Component *(I(share with VGA IN 1)) Video *1 Audio in (L/R)-RCA*2 S-Video *1 (share with VGA IN 1) HDMI*2 USB-A*1 USB-B*1
Output	VGA*1 (Share with VGA IN 2) Audio out (mini-jack,3.5mm) *1
Control	RS 232*1 RJ45*1.
Speakers	1* 10W
H-Synch Range	15-100KHz
H-Synch Range	15-100KHz
Computer Signal Input	VGA, SVGA, XGA, SXGA,WXGA,UXGA,WUXGA,Mac,
Video Signal Input	PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, PAL-60, 480i, 480p, 576i, 576p, 720p, 1080p and 1080i
Power Supply Voltage	100-240V@ 50/60Hz
Power Consumption	270W
ECO Standby Mode Power Consumption	<0.5W

Operating Temp	0°C-40°C(35- ECO)
Store Temp	-20°C--60°C
Operating Humidity	20%-85%
Storage Humidity	10%-85%
OSD Languages	26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch ,Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korea, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak,Vietnamese,Thai, Farsi
Projector Dimensions (WxHxD mm)	347*258*109
Net. Weight (KG)	3.2
Standard Accessories	Power cord, VGA cable,Remote control & RC Battery User manual(CD)