

SP Series

SP12-120 12V120Ah



SP series VRLA battery uses AGM technology and high-purity raw materials. Its good floating back up and large current discharge performance makes it optimal and economical choice for UPS/EPS.

Benefits

- Long life according to EUROBAT Classification
- Maximum charge efficiency
- High gas recombination efficiency
- Low self-discharge rate
- Easy installation and handling
- Vertical or horizontal installation


Applications

- UPS units
- Emergency power
- Starting generators
- EPS units

Standards

- IEC 60896-21/22
- JIS C8704-1/2
- EUROBAT guide

Drawing



Specifications


Battery Model	SP12-120			
Design Life (years, 25°C)	10			
Capacity (Ah, 25°C)	20HR (6.2.0A, 1.80V)	10HR (12A, 1.80V)	5HR (20.4A, 1.75V)	1HR(68.0A, 1.70V)
	124	120	102	68
Dimensions (mm)	Length	Width	Height	Total Height
	375	174	219	227
Approx. Weight (kg)	33.8			
Reference Internal Resistance (mΩ)	4.1 (full charged @ 25°C)			
Maximum Discharge Current (A/5 Sec.)	1200			
Self-Discharge (25°C)	≤ 2% per month			
Charge Voltage (V/cell, 25°C)	Cycle use		Float use	
	2.40 (-3.5mV/°C/cell), max charge current: 36 A		2.27 (-3.5mV/°C/cell)	
Short Circuit Current (A)	2900			

Discharge Data


Constant Current Discharge Data (25°C, A)													
End Voltage (V/cell)	min						h						
	5	10	15	20	30	45	1	1.5	2	3	5	10	20
1.60	372.0	280.0	217.0	174.5	132.0	97.50	71.60	56.52	44.50	32.20	21.73	12.40	6.550
1.65	366.0	275.0	213.0	170.0	128.9	95.90	69.80	55.75	43.64	31.79	21.25	12.32	6.450
1.67	359.2	270.0	209.4	167.3	127.7	94.89	69.05	55.35	43.28	31.58	21.04	12.30	6.422
1.70	351.0	264.0	205.0	163.9	126.0	93.50	68.00	54.72	42.74	31.24	20.75	12.25	6.370
1.75	317.0	243.0	193.0	157.4	122.0	90.00	66.00	53.45	42.00	30.60	20.40	12.18	6.300
1.80	268.0	219.6	179.0	146.8	114.0	85.00	63.00	51.00	40.50	29.50	19.70	12.00	6.200

Constant Power Discharge Data (25°C, W/cell)													
End Voltage (V/cell)	min						h						
	5	10	15	20	30	45	1	1.5	2	3	5	10	20
1.60	615.0	470.0	370.0	301.8	237.0	177.0	134.5	105.0	82.79	60.49	40.31	24.84	13.14
1.65	610.0	465.0	365.0	296.7	232.4	174.9	131.7	104.0	81.86	59.82	39.79	24.60	12.94
1.67	601.4	460.9	361.7	294.2	230.3	173.5	129.9	103.7	81.56	59.63	39.71	24.53	12.91
1.70	590.4	455.0	357.0	290.5	227.3	171.5	128.9	103.0	80.93	59.20	39.48	24.41	12.83
1.75	540.0	425.0	342.0	282.6	221.7	168.1	126.5	101.4	80.15	58.63	39.02	24.20	12.65
1.80	460.0	387.0	320.0	269.1	215.0	163.0	123.2	99.00	78.70	57.50	38.50	23.90	12.46


Performance Curve




Discharge voltage vs. discharge time



Charge capacity vs. charge time



Discharge capacity vs. temperature



Design life vs. temperature

Sacred Sun Power Sources Co., Ltd.

Add: No.1 Shengyang Road, Qufu 273100 PRC
 Tel: +86-537-4422313 Fax: +86-537-4411980
 Email: sales@sacredsunsun.cn

Sacred Sun Hong Kong Co., Limited

Add: RM 19C Lockhart CTR 301-307 Lockhart RD Wan Chai, Hong Kong
 Email: admin.hk@sacredsunsun.hk

Sacred Sun Asia Pacific Pte Ltd.

Add: 1 Ubi View, #04-12, Focus One, Singapore 408555
 Email: admin.sg@sacredsunsun.sg

Sacred Sun Europe SARL

Add: ZAE Fontaine, 33210 Fargues, France
 Email: admin.eu@sacredsunsun.eu

Sacred Sun MEA FZE

Add: No. 311 office, Building LOB 14, JAFZA, Dubai, UAE
 Email: admin.ae@sacredsunsun.ae

